


Nailbase

A one-step insulation and nailable surface.

Branch River nailbase consists of $\frac{7}{16}$ " Exposure I rated Oriented Strand Board (OSB) and UL Classified Branch River rigid insulation. It is an ideal insulation and nailable surface for structural roof decks and walls. Stability and traffic resistance make Branch River nailbase perfect for both residential/commercial roof decks and walls.

- Saves labor with one-step installation
- Large size panels available
- Saves energy - no thermal breaks
- Outside installation - construction can occur without disruption of inside living areas

Thickness/R-value.

 Thickness	R-value ¹	
	75°F ²	40°F ³
2	6.6	7.0
4	14.2	15.4
6	22.0	23.7
7 $\frac{3}{4}$	28.8	31.0
9 $\frac{3}{4}$	36.5	39.3
11 $\frac{3}{4}$	44.2	47.7


¹ R-value units are °F-ft²-h/Btu.

² Recommended for design in WARM climates.

³ Recommended for design in COLD climates.

Proven to meet, or exceed, building codes.

Branch River nailbase is manufactured under an industry leading quality control program monitored by UL and further recognized in UL Evaluation Report UL ER40326-01. Branch River meets ASTM C578, "Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation".



FOAM FACTS:

Branch River nailbase outperforms other nailbase products.

- Branch River nailbase can easily vary thickness to meet project R-values
- Branch River nailbase is less-expensive than XPS and ISO products
- No long-term R-value loss or thermal drift
- Branch River nailbase with borate treatment available to provide termite resistance

Energy Code Ci Requirements.

The use of continuous insulation is mandated by the 2012 International Energy Conservation Code (IECC). The IECC provides a prescriptive path for roof/ceiling insulation that includes the use of continuous insulation

Zone	IECC-2012 Prescriptive Ci R-value		
	Residential	Commercial	
	Ceiling	Roof Above Deck	
		All other	Group R
1	R-30	R-20ci	R-20ci
2	R-38	R-20ci	R-20ci
3	R-49	R-20ci	R-20ci
4 except Marine	R-49	R-25ci	R-25ci
5 and 4 Marine	R-49	R-25ci	R-25ci
6	R-49	R-30ci	R-30ci
7	R-49	R-35ci	R-35ci
8	R-49	R-35ci	R-35ci

Installation.

Installation shall be in strict accordance with published instructions, details, and drawings that are part of the contract documents for the project.

1. Branch River nailbase must be installed over a structurally sound roof deck.

2. Apply vapor retarder as specified by a qualified design professional prior to the installation of the Branch River nailbase.

Note: Climate conditions, code requirements, and building science dictate the use and position of vapor retarders within roof assemblies. Consult with local code officials and building science professional concerning the use of vapor retarders.

3. Install Branch River nailbase and mechanically fasten with Branch River Screws as specified.

4. Install continuous wood blocking at perimeters, ridges, hips, and openings as specified.

5. Install roof cladding materials per manufacturer's specifications and recommendations.

Ready to take control? Start here.

If you're ready to have Branch River contribute to your next project, just contact your Branch River Plastics, Inc. Technical Sales Representative. They will be happy to give you design consultation, information about Branch River products, pricing, and answers to all of your questions.



PLASTICS, INC.

15 Thurber Boulevard

Smithfield, RI 02917

P: 401-232-3434

www.branchriver.com



Branch River insulation products are manufactured by Branch River Plastics, Inc.

Copyright © 2020 Branch River Plastics, Inc.

UL logo is a registered trademark of UL LLC.

BRPNB01-11/20



www.branchriver.com

**NAILABLE
WALL AND ROOF
INSULATION**